



Pipe Inline Inspection Project

Tesoro Marine's 2008 Pipeline ILLI Project uses an HL250M Pump to run a special tool from the Tesoro refinery to the off shore tanker terminal. With the pump being able to meet the requirements, the tool inspects the inside of the pipelines.



The field test took place Apr 2-3/08 and Tesoro is planning to operate the project in September. Another use of this pump is in an emergency environmental disaster situation, Tesoro will run the pump to flush out fuel/oil lines.



The Godwin Dri-Prime 12" x 10" HL250M is a heavy duty, fully automatic self-priming pump specifically offered for pumping under discharge pressure conditions or high discharge lift applications. The HL250M offers flowrates up to 5,700 gpm, total dynamic heads up to 390 feet, and solids handling up to 3" in diameter. Like all Godwin pumps, the HL250M includes the Dri-Prime air ejector priming system for fully automatic priming up to 28 feet of static suction lift.





The Pacific Pipeline

The Monthly Newsletter of Pacific Pump and Power, Distributor of Godwin Pumps®

Rental • Sales • Service

May 2008

godwin pumps



52 Pumps, Generators and Light Plants Available for Rent or Purchase in Hawaii

Pump Type	Quantity Available	Pump Model and Description
Godwin Dri-Prime CD Series, High Volume, Medium Head, Large Solids-Handling Capabilities	32 AVAILABLE	<ul style="list-style-type: none"> •DPC300 12" Diesel, up to 5000 gpm or up to 115' of head •DPC300 12" Electric, up to 4000 gpm or up to 115' of head •CD225M 8" Diesel, up to 3100 gpm or up to 183' of head •CD225M 8" Electric, up to 3100 gpm or up to 175' of head •CD150M 6" Diesel, up to 1700 gpm or up to 160' of head •CD103M 4" Diesel, up to 1000 gpm or up to 170' of head •CD100M 4" Diesel, up to 750 gpm or up to 115' of head •CD80M 3" Diesel, up to 450 gpm or up to 93' of head
Godwin HL Series, High Head pump with Solids-Handling Capabilities	7 AVAILABLE	<ul style="list-style-type: none"> •HL5M 6" Diesel, up to 1450 gpm or up to 500' of head •HL80M, 3" Diesel, up to 450 gpm or up to 325' of head
Godwin Heidra Hydraulic Submersibles	2 AVAILABLE	<ul style="list-style-type: none"> •HS150VSG 6", Diesel, up to 1600 gpm or up to 160' of head •HS100TD 4", Diesel, up to 800 gpm or up to 130' of head
Godwin Sub-Prime Electric Submersibles	7 AVAILABLE	<ul style="list-style-type: none"> •GSP600SV, 8", up to 3650 gpm or up to 82' of head •GSP160HV, 6", up to 1200 gpm or up to 115' of head •GSP55, 4", up to 550 gpm or up to 75' of head •GSP10-115, 2", up to 90 gpm or up to 60' of head
Godwin Wet-Prime Gas Trash Pumps	1 AVAILABLE	•GTP80HX, 3"
Godwin Versamatic Diaphragm Pumps	3 AVAILABLE	<ul style="list-style-type: none"> •Versamatic Air Operated E3, 3" Pumps on their way!! •Versamatic Air Operated E2, 2", up to 155gpm •Versamatic Air Operated E4, 1½" x 1¼", up to 70gpm
Godwin Power Diesel Generator Sets	1 AVAILABLE	•26kW-R Series, Critically Silenced
Gasoline Generator Sets	2 AVAILABLE	•3000, 5000 Watt, Portable Honda Model
Godwin Portable Light Tower	3 AVAILABLE	•GLT 416, 4000 Watts, Coverage of 5-7 acres
Road Ramp Crossings	10 AVAILABLE	•4", 6", 8" and 12" Road Ramps Crossings
Hydraulic Hose	800 FEET	•¼", ½", ¾" and 1" Hydraulic Hose with Couplers
Heavy Duty Hose	5440 FEET	•2", 3", 4", 6", 8", and 12" Heavy Duty Suction and Discharge Hose Available with Quick Disconnect Fittings
Bauer Light Weight, Quick Disconnect Pipe	5780 FEET	•4", 6", 8", and 12" Bauer Light Weight Quick Disconnect Pipe in 10' and 20' Lengths
Pump Accessories	3700 IN STOCK	•Bauer and Camlock Fittings from 2-12" Available
Pump Parts	700 IN STOCK	•Common Wear Parts for all Pumps Already in Stock
Cherne Pipe Plugs	10 AVAILABLE	•8-12", 12-24", 15-30" and 24-42" with Sleeves and Inflators

Pacific Pump and Power welcomes
Jonah Tenorio to our team!!!



Above: Jonah Tenorio and Patrick Baker



For immediate assistance please contact Patrick Baker: 721-0264 or Jeremy Leonard: 721-0127

Call today at 672-8198 or visit us at Campbell Industrial: 91-503 Nukuawa Street, Kapolei