
he TR-Series are large volume, high pressure hydrostatic pumps. Designed for testing boilers, vessels, process piping, steam and gas lines. The ceramic plunger pump, has

## Model TR-Series • Up to 5.5GPM • 5000PSI





Ξ

0

C

0

10

**d** 

3

2

≥



- Automatic Pressure Regulator with Inlet Bypass
- Stainless Steel Liquid-Filled Gauge Ensure Accurate Readings, with Less Flutter
- Enclosed in a Rugged Roll Cage & Heavy Gauge Steel Base
- Stainless Steel Ballvalve to Isolate Pressure

TR	S	E P	RIE	S	
Pump	TRH-2	TRE-6	TRH-8	TRE-8	TRH-10
PSI	2000	2700	3600	3600	5000
GPM	3	4	4	4	4.5
Inlet	3/4"	3/4"	3/4"	3/4"	3/4"
Outlet	3/8"	3/8"	3/8"	3/8"	3/8"
Motor/Engine	Honda 163 CC	Baldor 7 1/2 HP 60 HZ	Honda 13 HP 389 CC	Baldor 10 HP 60 HZ	Honda 20 HP 614 CC
Shipping Dimensions	25X21X17	35X25X19	35X <mark>25X1</mark> 9	35X25X19	35X25X21
Shipping Weight	120 lbs.	255 lbs.	177 <mark>lbs.</mark>	286 lbs.	250 lbs.
Options:Engines: Briggs & Stratton, Honda or DieselMotors:Explosion proof, Variation in Hertz, Voltage and Phase					



3500 Arrowhead Drive Carson City Nevada 89706 web site: www.ricehydro.com e-mail: ricehydro@ricehydro.com Phone: (775) 885-1280

Fax: (800) 998-7423

## Hydrostatic Test Pumps 🖒 Post Hole Diggers